

# Maryland Steam Historical Society Fun Tractor Pull

***\*Please Note: Rules are Subject to Change\****

## **General Information:**

A \$10 membership must be purchased to pull.

- There will be a \$15 hook fee.
- Signed agreement with any parent or legal guardian for children under the age of 16. Minimum age of 13 years old.
- No alcohol.
- There will be no rain date.
- There is a 3-hook limit per tractor.

## **Weight Classes:**

- 4500lb • 5500lb • 6500lb • 7500lb • 8500lb • 10500lb • 12500lb • 14500lb
- All weight classes will have a 4MPH, 6MPH, and Open
- All tractor-pulling committee decisions are final.
- No offensive language should be used against other pullers or track staff/committee members – their decisions will be final.
- 100lb allowance for all weight classes.
- Tractors must have all quantity equipped wheels.
- Operators of all ages must be able to operate tractors safely.
- The front of the frame to the front of the front weight bracket must be 20 inches or under.
- Operators must adhere to and respond to the flagger, or the operator will be disqualified from that class.
- Tractor must be in neutral gear, and hands cleared in order to be hooked and unhooked to the sled.
- Tractors must stay within marked boundaries, or they will be disqualified from the class.
- Closed-toed shoes must be worn to pull.
- There will be a mandatory safety meeting 15 minutes before the start of the pull.
- 1<sup>st</sup> puller in the class will have the option to be able to pull again in 3<sup>rd</sup>.
- Pullers that stop before 50ft will have the option to restart.

- Pullers will have a 2-horn allowance, after the third, the puller will be disqualified from that class.
  - If the tractor is equipped with four-wheel drive, it must be in two-wheel drive.
  - Tractors must be hooked to the sled within 2 minutes of your hook, if not, the puller will be moved to the end of the class.
  - No pulling off the 3-point hitch. Fast hitches must be pinned or fixed.
  - No steel wheels, tracks, or duals.
  - Clevis rings will have to be 3 inches wide and 3 ¾ inches from the rear of the drawbar. (Inside measurement)
- THE CLUB WILL NOT PROVIDE A CLEVIS**
- Pulling hitch holes must be 3 inches wide and 3 ¾ inches deep.

## **Antique Class**

- Tractors will be limited to running up to 4mph.
- Tractors cannot be newer than 1965.
- Tractors must have manufacturer-brand engines.
- Tractors can only run off gas, diesel, or propane.
- Max tire size- 15.5-38, 18.4-34.
- 10% over factory RPMs.
- Wheel weights may not extend more than 16 inches from the hub, where the wheel attaches to the axel.
- No headers.
- No cut tires.
- Hitches must not be shorter than 18 inches from the center of the axle to the hitch point and cannot exceed 18 inches from the ground to the hitch point unless equipped with wheelie bars and cannot exceed 20 inches.

## **Altered Class**

- Tractors cannot be newer than 1975.

- Tractors will be limited to running up to 6mph.
- Tractors must have manufacturer-brand engines.
- Tractors can only run off gas, diesel, or propane.
- Cut or altered tires are allowed.
- Max tire sizes- 23.1-34, 18.4-38.
- Hitches must not be shorter than 18 inches from the center of the axle to the hitch point and cannot exceed 18 inches from the ground to the hitch point unless equipped with wheelie bars and cannot exceed 20 inches.

### **“Vintage Outlaw” (Open) Class**

- Tractors cannot be newer than 1975.
- Tractors are NOT limited to rpm or speed.
- ROPS is highly recommended at this time. Subject to change.
- Kill switch is required – must work.
- Cut or altered tires are allowed.
- Tractors can only run on gas, diesel, or propane.
- Hitches must not be shorter than 18 inches from the center of the axle to the hitch point and must not exceed 20 inches from the ground.
- Wheelie bars are required – Pads may NOT be over 10 inches from the ground and a minimum of 32 inches rearward from the rear axle. There must be bumper bars that extend at least 12 inches from the pads. Pads must be 20 inches apart and at least 5 inches square.
- Tractors are required to have side shields and blow-proof blankets are required for any tractor over 3000 rpm.
- Tractors that are high speed (12mph and over) are also required to have seats with 8-inch back support minimum and fenders.
- Rollover protection and seat belts are highly recommended. A factory-built or certified rollbar is preferred.
- **Turbocharger cross bolts are highly recommended. 3/8 bolts required.**